



Revision Date: 08/04/2015

SAFETY DATA SHEET

1. Identification

Identification

Product name: PARATHERM™ CR

Additional identification

Chemical name: Diethylbenzenes

Recommended use and restriction on use

Recommended use: Heat Transfer Fluid

Restrictions on use: Lubricating oils; Hydraulic fluid additive

Details of the supplier of the safety data sheet

Supplier

Company Name: PARATHERM

A DIV. OF THE LUBRIZOL CORPORATION

Address: 31 PORTLAND ROAD

WEST CONSHOHOCKEN, PA 19428

US

Telephone: 610-941-4900

Emergency telephone number:

FOR TRANSPORT EMERGENCY CALL CHEMTREC (+1)703 527 3887, OR WITHIN USA 800 424 9300 (LUBRIZOL)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids Category 3

Health Hazards

Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Category 1

Irritation

Specific Target Organ Toxicity - Category 3

Single Exposure

Aspiration Hazard Category 1

Unknown toxicity

Acute toxicity, oral 0.0 %
Acute toxicity, dermal 0.0 %
Acute toxicity, inhalation, vapor 99.9 %
Acute toxicity, inhalation, dust 100.0 %
or mist

Label Elements:

Hazard Symbol:











Revision Date: 08/04/2015

Signal Word: Danger

Hazard Statement: Flammable liquid and vapor.

Causes skin irritation.

Causes serious eye damage. May cause respiratory irritation.

May be fatal if swallowed and enters airways.

Precautionary Statement:

Keep away from heat, hot surfaces, sparks, open flames and Prevention:

other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Avoid release to the

environment.

Response: IF INHALED: Remove person to fresh air and keep comfortable

> for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin

irritation occurs: Get medical advice/attention. IF

SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. Immediately call a POISON

CENTER/doctor. Specific treatment (see this label). Take off contaminated clothing. In case of fire: Use CO2, dry chemical or foam for extinction. Water can be used to cool and protect

exposed material. Collect spillage.

Store in well-ventilated place. Keep cool. Keep container tightly Storage:

closed. Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and

disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Other hazards which do not result

in GHS classification:

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

General information:

Chemical name	CAS number	Percent by Weight
Diethylbenzenes	25340-17-4	60 - 70%
Dibutyl ether	142-96-1	30 - 40%
++ 1,3-Diethyl benzene	141-93-5	40 - 50%
++ Diethylbenzene	105-05-5	10 - 20%
++ Diethylbenzene	135-01-3	1 - 5%

⁺⁺ The listed components are subcomponents of the hazardous ingredients listed above.



Revision Date: 08/04/2015

4. First-aid measures

Ingestion: Do NOT induce vomiting. Aspiration of material due to vomiting can cause

chemical pneumonitis which can be fatal. If vomiting occurs naturally, the casualty should lean forward to reduce the risk of aspiration. Rinse mouth.

Immediately call a POISON CENTER/doctor/...

Inhalation: Remove exposed person to fresh air if adverse effects are observed.

Skin Contact: Take off immediately all contaminated clothing. Take off contaminated

clothing and wash before re-use. Wash skin thoroughly with soap and

water. If skin irritation occurs, get medical attention.

Eye contact: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/doctor/...

Most important symptoms/effects, acute and delayed

Symptoms: See section 11.

Indication of immediate medical attention and special treatment needed

Treatment: Treat symptomatically.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Water may be

ineffective in fighting the fire. Fight fire from a protected location. Move

containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

CO2, Dry chemical or Foam. Water can be used to cool and protect

exposed material.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations. Vapors may travel

considerable distance to a source of ignition and flash back. Water may cause splattering. Container may rupture on heating. A solid stream of water will spread the burning material. Material creates a special hazard because it floats on water. See section 10 for additional information.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective

equipment for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.



Revision Date: 08/04/2015

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep upwind. Keep unauthorized personnel away. See Section 8 of the SDS for Personal Protective Equipment.

Methods and material for containment and cleaning up:

Eliminate all ignition sources if safe to do so. Dike far ahead of larger spill for later recovery and disposal. Pick up free liquid for recycle and/or disposal. Residual liquid can be absorbed on inert material. Stop the flow of material, if this is without risk. Prevent entry into waterways, sewer, basements or confined areas.

Environmental Precautions:

Avoid release to the environment. Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges. Ground/bond container and receiving equipment. Use only non-sparking tools. Do not get in eyes. Avoid contact with skin. Observe good industrial hygiene practices. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Launder contaminated clothing before reuse. Avoid environmental contamination.

Maximum Handling Temperature:

Not determined.

Conditions for safe storage,

including any incompatibilities:

Keep container tightly closed. Keep cool. Store in a well-ventilated place.

Do not store near potential sources of ignition.

Maximum Storage Temperature:

Not determined.

8. Exposure controls/personal protection

Control Parameters:

Occupational Exposure Limits

None of the components have assigned exposure limits.

Appropriate engineering

controls:

Use explosion-proof ventilation equipment to stay below exposure limits.

Individual protection measures, such as personal protective equipment

General information: Use explosion-proof ventilation equipment. Provide easy access to water

supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation,

or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Eye/face protection: Wear tight-fitting goggles or face shield.



Revision Date: 08/04/2015

Skin Protection

Hand Protection: Use nitrile or neoprene gloves. Use good industrial hygiene practices. In

case of skin contact, wash hands and arms with soap and water.

Other: Wear apron or protective clothing in case of contact. Do not wear rings,

watches or similar apparel that could entrap the material.

Respiratory Protection: A respiratory protection program compliant with all applicable regulations

must be followed whenever workplace conditions require the use of a respirator. Under normal use conditions, respirator is not usually required. Use appropriate respiratory protection if exposure to dust particles, mist or vapors is likely. Use self-contained breathing apparatus for entry into confined space, for other poorly ventilated areas and for large spill clean-up

sites.

Hygiene measures: Observe good industrial hygiene practices. Do not get in eyes. Avoid

contact with skin. Wash contaminated clothing before reuse. When using do not smoke. Wash hands before breaks and immediately after handling

the product.

9. Physical and chemical properties

Appearance

Physical state: liquid Form: liquid

Color: Colorless to white

Odor: Sweet

Odor threshold:No data available.pH:No data available.Freezing point:No data available.Boiling Point:358 °F (181 °C)

Flash Point: > 102 °F (39 °C) (ASTM D 93 (Pensky-Martens Closed Cup))

Evaporation rate: < 1 n-butyl acetate=1 **Flammability (solid, gas):** No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper (%):

No data available.

No data available.

No data available.

No data available.

Vapor pressure:

< 10 torr (21 °C 70 °F)

Vapor density: > 1

Relative density: 0.831 - 0.837 60.1 °F (15.6 °C)

Solubility(ies)

Solubility in water:
Solubility (other):
No data available.
Partition coefficient (n-octanol/water):
No data available.
No data available.
Decomposition temperature:
No data available.
No data available.

Viscosity: < 0.8 mm2/s (104 °F (40 °C))

10. Stability and reactivity

Reactivity: No data available.



Revision Date: 08/04/2015

Chemical Stability: Material is stable under normal conditions.

Possibility of Hazardous

Reactions:

Will not occur.

Conditions to Avoid: Heat, sparks, flames.

Incompatible Materials: None known, avoid contact with reactive chemicals.

Hazardous Decomposition

Products:

Thermal decomposition or combustion may generate smoke, carbon monoxide, carbon dioxide, and other products of incomplete combustion.

11. Toxicological information

Information on likely routes of exposure

Inhalation: No data available.

Ingestion: May be harmful if swallowed.

Skin Contact: Causes skin irritation.

Eye contact: Causes serious eye damage.

Information on toxicological effects

Acute toxicity

Oral

Product: ATEmix > 2000 mg/kg.

Dermal

Product: Not classified for acute toxicity based on available data.

Inhalation

Product: High concentrations may cause headaches, dizziness, nausea,

behavioral changes, weakness, drowsiness and stupor. Not classified for acute toxicity based on available data.

Skin Corrosion/Irritation:

Product: Prolonged or repeated skin contact as from clothing wet with

material may cause dermatitis. Symptoms may include redness,

edema, drying, and cracking of the skin.

Remarks: Causes skin irritation.

Serious Eye Damage/Eye Irritation:

Product: Remarks: Causes serious eye damage.

Respiratory sensitization:

No data available

Skin sensitization:

No data available

Specific Target Organ Toxicity - Single Exposure:

++ 1,3-Diethyl benzene Nose, throat and lung irritant.

Dibutyl ether May cause respiratory irritation.

Aspiration Hazard:

Product: May be fatal if swallowed and enters airways.



Revision Date: 08/04/2015

Chronic Effects

Carcinogenicity:

No data available

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity:

Diethylbenzenes This material has not exhibited mutagenic or genotoxic potential in

laboratory tests.

Reproductive toxicity:

No data available

Specific Target Organ Toxicity - Repeated Exposure:

Diethylbenzenes Prolonged or repeated exposures may result in adverse effects on

the liver, kidney and/or nervous system.

Unknown: Target Organ(s): Kidney, Liver, Central nervous system.

++ Diethylbenzene Oral: Target Organ(s): Liver

12. Ecological information

Ecotoxicity

Fish

Diethylbenzenes LC 50 (Rainbow Trout, 4 h): 0.673 mg/l

Aquatic Invertebrates

Diethylbenzenes EC 50 (Water flea (Daphnia magna), 2 d): 2.01 mg/l

Dibutyl ether EC 50 (Water flea (Daphnia magna), 2 d): 26 mg/l

++ Diethylbenzene EC 50 (Water flea (Daphnia magna), 1 d): 32 mg/l

EC 50 (Water flea (Daphnia magna), 21 d): 2.4 mg/l

Toxicity to Aquatic Plants

Diethylbenzenes LC 50 (Green algae (selenastrum capricomutum), 3 h): 1.21 mg/l

Toxicity to soil dwelling organisms

No data available

Sediment Toxicity

No data available

Toxicity to Terrestrial Plants

No data available

Toxicity to Above-Ground Organisms

No data available



Revision Date: 08/04/2015

Toxicity to microorganisms

No data available

Persistence and Degradability

Biodegradation

Diethylbenzenes Miscellaneous, 4.7 %, 28 d, Not readily degradable.

++ Diethylbenzene 1.6 %, Not readily degradable.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

No data available

Partition Coefficient n-octanol / water (log Kow)

++ Diethylbenzene Log Kow: 0.1

Mobility:

No data available

Other Adverse Effects: No data available.

13. Disposal considerations

Disposal instructions: Treatment, storage, transportation, and disposal must be in accordance

with applicable Federal, State/Provincial, and Local regulations.

Dispose of packaging or containers in accordance with local, regional, national and international regulations. Empty containers retain material residue. Do not cut, weld, braze, solder, drill, grind or expose containers to

heat, flame, spark or other sources of ignition.

Contaminated Packaging: Container packaging may exhibit hazards.

14. Transport information

DOT

UN Number: NA 1993

UN Proper Shipping Name: Combustible liquid, n.o.s.

Transport Hazard Class(es)

Class: CBL
Label(s): NONE
Packing Group: III
Marine Pollutant: Yes

Special precautions for user:

Reportable quantity

None established

Dibutyl ether 100 lbs



Revision Date: 08/04/2015

IMDG

UN Number: UN 3295

UN Proper Shipping Name: HYDROCARBONS, LIQUID, N.O.S.

Transport Hazard Class(es)

 Class:
 3

 Label(s):
 3

 EmS No.:
 F-E, S-D

Packing Group: III
Marine Pollutant: Yes
Limited quantity 5.00L

Excepted quantity E1

Special precautions for user: None established

IATA

UN Number: UN 3295

Proper Shipping Name: Hydrocarbons, liquid, n.o.s.

Transport Hazard Class(es):

Class: 3
Label(s): 3

Marine Pollutant: Yes
Packing Group: III
Limited quantity 10.00L

Excepted quantity E1

Environmental Hazards Marine Pollutant Special precautions for user: None established

Other information

Passenger and cargo aircraft: Allowed. Cargo aircraft only: Allowed.

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

None known.

Shipping descriptions may vary based on mode of transport, quantities ,temperature of the material, package size, and/or origin and destination It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material. Review classification requirements before shipping materials at elevated temperatures.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

None known.

SARA 302 Extremely Hazardous Substance

SARA 304 Emergency Release Notification

SARA 311/312 Hazardous Chemical

SARA 313 (TRI Reporting)

This product may contain chemical(s) regulated under the Superfund Amendments and Reauthorization Act (SARA). For additional information please contact Lubrizol Customer Assistance: America(s): AmerLZAMCustomerAssistance@Lubrizol.com; Europe: EMEAICustomerAssistance@Lubrizol.com; Asia: APCustomerAssistance@Lubrizol.com

Revision Date: 08/04/2015

US State Regulations

US. California Proposition 65

No ingredient regulated by CA Prop 65 present.

Inventory Status

Australia (AICS)

All components are in compliance with chemical notification requirements in Australia.

Canada (DSL/NDSL)

All components are in compliance with the Canadian Environmental Protection Act and are present on the Domestic Substances List.

China (IECSC)

All components of this product are listed on the Inventory of Existing Chemical Substances in China.

European Union (REACh)

To obtain information on the REACH compliance status of this product, please visit Lubrizol.com/REACH, or e-mail us at REACH_MSDS_INQUIRIES@Lubrizol.com

Japan (ENCS)

All components are in compliance with the Chemical Substances Control Law of Japan.

Korea (ECL)

All components are in compliance in Korea.

New Zealand (NZIoC)

All components are in compliance with chemical notification requirements in New Zealand.

Philippines (PICCS)

All components are in compliance with the Philippines Toxic Substances and Hazardous and Nuclear Wastes Control Act of 1990 (R.A. 6969).

Switzerland (SWISS)

All components are in compliance with the Environmentally Hazardous Substances Ordinance in Switzerland.

Taiwan (TCSCA)

All components of this product are listed on the Taiwan inventory.

United States (TSCA)

All components of this material are on the US TSCA Inventory.

The information that was used to confirm the compliance status of this product may deviate from the chemical information shown in Section 3.

16.Other information, including date of preparation or last revision

HMIS Hazard ID




Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe; RNP - Rating not possible; *Chronic health effect



Revision Date: 08/04/2015

NFPA Hazard ID



Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe; RNP - Rating not possible

Issue Date: 08/04/2015

Version #: 1.1

Source of information: Internal company data and other publically available resources.

Further Information: Contact supplier (see Section 1)

Disclaimer: As the conditions or methods of use are beyond our control, we do not

assume any responsibility and expressly disclaim any liability for any use of this product. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with all applicable federal, state, and local regulations remains

the responsibility of the user.