

SAFETY DATA SHEET

1. Identification

Identification

Product name: PARATHERM™ LC

Additional identification

Chemical name: Alkylphenol

Recommended use and restriction on use

Recommended use: Heat Transfer Fluid

Restrictions on use: Lubricating oils; Hydraulic fluid additive

Details of the supplier of the safety data sheet

Supplier

Company Name: PARATHERM
A DIV. OF THE LUBRIZOL CORPORATION
Address: 2009 Renaissance Boulevard
King of Prussia, PA 19406
US
Telephone: 610-941-4900

Emergency telephone number:

FOR TRANSPORT EMERGENCY CALL CHEMTREC (+1)703 527 3887, OR WITHIN USA 800 424 9300

2. Hazard(s) identification

Hazard Classification

Health Hazards

Toxic to reproduction Category 2

Unknown toxicity

Acute toxicity, oral	0.0 %
Acute toxicity, dermal	0.0 %
Acute toxicity, inhalation, vapor	100.0 %
Acute toxicity, inhalation, dust or mist	79.0 %

Label Elements:

Hazard Symbol:



Signal Word: Warning

Hazard Statement: Suspected of damaging fertility or the unborn child.

Precautionary Statement:

- Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
- Response:** If exposed or concerned: Get medical advice/attention.
- Storage:** Store locked up.
- Disposal:** Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Other hazards which do not result in GHS classification: None identified.

3. Composition/information on ingredients

Chemical name	CAS number	Percent by Weight
Mineral oil	8042-47-5	40 - 50%
p-Dodecylphenol	74499-35-7	1 - 5%
Ethylene glycol	107-21-1	1 - 5%

4. First-aid measures

- General information:** IF exposed or concerned: Get medical advice/attention.
- Ingestion:** Rinse mouth. Get medical attention if symptoms occur.
- Inhalation:** Remove exposed person to fresh air if adverse effects are observed.
- Skin Contact:** Take off contaminated clothing and wash before re-use. Wash with soap and water. If skin irritation occurs, get medical attention. Launder contaminated clothing before reuse.
- Eye contact:** Flush thoroughly with water. If irritation occurs, get medical assistance. Remove contact lenses, if present and easy to do. Continue rinsing.

Most important symptoms/effects, acute and delayed

Symptoms: See section 11.

Indication of immediate medical attention and special treatment needed

Treatment: Treat symptomatically.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: CO₂, Dry chemical or Foam. Water can be used to cool and protect exposed material.

Unsuitable extinguishing media: Not determined.

Specific hazards arising from the chemical: When heated, hazardous gases may be released including: sulfur dioxide. See section 10 for additional information. Material creates a special hazard because it floats on water. A solid stream of water will spread the burning material.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Recommend wearing self-contained breathing apparatus.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Personal Protective Equipment must be worn, see Personal Protection Section for PPE recommendations. Ventilate spill area.

Methods and material for containment and cleaning up: Dike far ahead of larger spill for later recovery and disposal. Pick up free liquid for recycle and/or disposal. Residual liquid can be absorbed on inert material.

Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Environmental manager must be informed of all major spillages. Do not contaminate water sources or sewer. Avoid release to the environment.

7. Handling and storage

Precautions for safe handling: Material can accumulate static charges which may cause an electrical spark (ignition source). Use proper bonding and/or grounding procedures. Use grounding and bonding connection when transferring material. In case of spills, beware of slippery floors and surfaces. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Observe good industrial hygiene practices. Provide adequate ventilation. Use personal protective equipment as required. Launder contaminated clothing before reuse. Avoid environmental contamination.

Maximum Handling Temperature: Not determined.

Conditions for safe storage, including any incompatibilities: Store away from incompatible materials. See section 10 for incompatible materials.

Maximum Storage Temperature: Not determined.

8. Exposure controls/personal protection

Control Parameters:

Occupational Exposure Limits

Chemical name	type	Exposure Limit Values	Source
Mineral oil - Inhalable fraction.	TWA	5 mg/m ³	US. ACGIH Threshold Limit Values (02 2012)
Mineral oil - Mist.	REL	5 mg/m ³	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
Mineral oil - Mist.	STEL	10 mg/m ³	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
Mineral oil - Mist.	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylene glycol	Ceiling	50 ppm 125 mg/m ³	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Ethylene glycol - Aerosol.	Ceiling	100 mg/m ³	US. ACGIH Threshold Limit Values (02 2012)

Appropriate engineering controls:

No special requirements under ordinary conditions of use and with adequate ventilation.

Individual protection measures, such as personal protective equipment

General information:

Use personal protective equipment as required.

Eye/face protection:

If contact is likely, safety glasses with side shields are recommended.

Skin Protection

Hand Protection:

Use nitrile or neoprene gloves. Use good industrial hygiene practices. In case of skin contact, wash hands and arms with soap and water. Gloves should always be inspected before each use and discarded if they show tears, pinholes, or signs of wear.

Other:

Gloves, coveralls, apron, boots as necessary to minimize contact.

Respiratory Protection:

Use disposable dust/mist mask if the recommended exposure limit is exceeded. A respiratory protection program compliant with all applicable regulations must be followed whenever workplace conditions require the use of a respirator. Under normal use conditions, respirator is not usually required. Use appropriate respiratory protection if exposure to dust particles, mist or vapors is likely. Use self-contained breathing apparatus for entry into confined space, for other poorly ventilated areas and for large spill clean-up sites.

Hygiene measures:

Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Observe good industrial hygiene practices.

9. Physical and chemical properties

Appearance

Physical state:

liquid

Form:

liquid

Color:

Dark brown

Odor:

Mild petroleum/solvent

Odor threshold:

No data available.

pH:

No data available.

Freezing point:	No data available.
Boiling Point:	> 700 °F (371 °C)
Flash Point:	> 350.1 °F (176.7 °C) (ASTM D93 (Pensky-Martens (A and B Closed Cup)))
Evaporation rate:	< 1 n-butyl acetate=1
Flammability (solid, gas):	No data available.
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	< 1 torr (21.1 °C 70.0 °F)
Vapor density:	> 1
Relative density:	0.94 60.01 °F (15.56 °C)
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	66.3 mm ² /s (104 °F (40 °C))

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	Will not occur.
Conditions to avoid:	Do not expose to excessive heat, ignition sources, or oxidizing materials.
Incompatible Materials:	Strong oxidizing agents.
Hazardous Decomposition Products:	Thermal decomposition or combustion may generate smoke, carbon monoxide, carbon dioxide, and other products of incomplete combustion.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	No data available.
Ingestion:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.

Information on toxicological effects

Acute toxicity

Oral

Product: Material can be aspirated into the lungs during the act of swallowing or vomiting. This could result in severe injury to the lungs and death. Ingestion can cause central nervous system effects such as headache, dizziness, drowsiness, and generalized weakness. ATEmix > 10,000 mg/kg.

Dermal

Product: Prolonged or widespread contact with this material could result in the absorption of potentially harmful amounts. Not classified for acute toxicity based on available data.

Inhalation

Product: Not classified for acute toxicity based on available data.

Skin Corrosion/Irritation:

Product: Prolonged or repeated skin contact as from clothing wet with material may cause dermatitis. Symptoms may include redness, edema, drying, and cracking of the skin. Prolonged or repeated exposure may cause a slight flaking, tenderness, and softening of skin.
Remarks: Not classified as a primary skin irritant.

Serious Eye Damage/Eye Irritation:

Product: Remarks: Not classified as a primary eye irritant.

Respiratory sensitization:

No data available

Skin sensitization:

Mineral oil Classification: Not a skin sensitizer. (Literature) Not a skin sensitizer.

p-Dodecylphenol Classification: Not a skin sensitizer. (Literature) Not a skin sensitizer.

Specific Target Organ Toxicity - Single Exposure:

Mineral oil If material is misted or if vapors are generated from heating, exposure may cause irritation of mucous membranes and the upper respiratory tract.

p-Dodecylphenol May cause irritation to the mucous membranes and upper respiratory tract.

Ethylene glycol If material is misted or if vapors are generated from heating, exposure may cause irritation of mucous membranes and the upper respiratory tract.

Aspiration Hazard:

Mineral oil Material can be aspirated into the lungs during the act of swallowing or vomiting. This could result in severe injury to the lungs and death.

Chronic Effects

Carcinogenicity:

No data available

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity:

p-Dodecylphenol

This material has not exhibited mutagenic or genotoxic potential in laboratory tests.

Reproductive toxicity:

p-Dodecylphenol

Suspected of damaging fertility.
Suspected of damaging fertility.

Ethylene glycol

In studies on rats, ethylene glycol has been shown not to interfere with reproduction. In studies on mice, ingestion of ethylene glycol in large amounts caused a small decrease in the number of litters per pair, live pups per litter, and in live pupweight. Based on animal studies, ingestion of ethylene glycol appears to be the major and possibly only route of exposure to produce birth defects. Exposures by inhalation (tested nose only in animals) or skin contact, the primary routes of occupational exposure, have minimal or essentially no effect on the fetus.

Specific Target Organ Toxicity - Repeated Exposure:

p-Dodecylphenol

This product contains para-dodecylphenol. Rats given high, repeated daily doses of para-dodecylphenol by oral intubation experienced effects on a number of organs including adrenal, thyroid, liver, ovary, testes, bone marrow and blood cell formation.

Ethylene glycol

Long term dietary intake of ethylene glycol caused liver and kidney effects and deposition of calcium salts in various tissues in animals. Excessive exposure may cause CNS effects, cardiopulmonary effects (metabolic acid-osis), and kidney failure.
Unknown: Target Organ(s): Lung

12. Ecological information

Ecotoxicity

Fish

Mineral oil

LC 50 (Not reported, 96 h): > 10,000 mg/l
NOEC (Not reported, 96 h): > 10,000 mg/l

p-Dodecylphenol

LC 50 (Fathead Minnow, 4 d): 40 mg/l

Ethylene glycol

LC 50 (Fathead Minnow, 4 d): 8,050 mg/l

Aquatic Invertebrates

Mineral oil
EC 50 (Water flea (Daphnia magna), 2 d): > 100 mg/l
NOEC (Water flea (Daphnia magna), 2 d): >= 100 mg/l
EC 50 (Water flea (Daphnia magna), 21 d): > 10 mg/l
NOEC (Water flea (Daphnia magna), 21 d): 10 mg/l

p-Dodecylphenol
EC 50 (Water flea (Daphnia magna), 2 d): 0.037 mg/l
EC 50 (Shrimp (Mysidopsis Bahia), 4 d): > 0.58 mg/l
EC 50 (Water flea (Daphnia magna), 21 d): 0.0079 mg/l
NOEC (Water flea (Daphnia magna), 21 d): 0.0037 mg/l

Toxicity to Aquatic Plants

Mineral oil
LC 50 (Algae (Pseudokirchneriella subcapitata), 3 d): > 100 mg/l
NOEC (Algae (Pseudokirchneriella subcapitata), 3 d): > 100 mg/l

p-Dodecylphenol
EC 50 (Green algae (Scenedesmus quadricauda), 2 d): 0.36 mg/l

Toxicity to soil dwelling organisms

No data available

Sediment Toxicity

No data available

Toxicity to Terrestrial Plants

No data available

Toxicity to Above-Ground Organisms

No data available

Toxicity to microorganisms

p-Dodecylphenol
EC 50 (Sludge, 0.1 d): > 1,000 mg/l

Persistence and Degradability

Biodegradation

Mineral oil
OECD TG 301 F, 31.13 %, 28 d, Not readily degradable.

p-Dodecylphenol
Miscellaneous, 10 %, 56 d, Not readily degradable.
OECD TG 301 B, 25 %, 28 d, Not readily degradable.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

p-Dodecylphenol
Bioconcentration Factor (BCF): 794.33 (Measured)

Partition Coefficient n-octanol / water (log Kow)

p-Dodecylphenol
Log Kow: 7.14 (Measured)

Mobility:

No data available

Other Adverse Effects:

No data available.

13. Disposal considerations

Disposal instructions: Treatment, storage, transportation, and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations. Dispose of packaging or containers in accordance with local, regional, national and international regulations. Empty container contains product residue which may exhibit hazards of product.

Contaminated Packaging: Container packaging may exhibit hazards.

14. Transport information
DOT

Not regulated.

IMDG

Not regulated.

IATA

Not regulated.

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

None known.

The DOT shipping information in this section is based on a bulk container. Please review the accompanying shipping papers for the correct shipping descriptions based the size of the package. Shipping descriptions may vary based on mode of transport, quantities, temperature of the material, package size, and/or origin and destination. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material. During transportation, steps must be taken to prevent load shifting or materials falling, and all relating legal statutes should be obeyed. Review classification requirements before shipping materials at elevated temperatures.

15. Regulatory information
US Federal Regulations
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4)

<u>Chemical Identity</u>	<u>CAS number</u>	<u>Reportable quantity</u>	<u>Calculated¹</u>
Ethylene glycol	107-21-1	5000 lbs	> 50000 lbs > 22680 kgs

¹This is the amount product/material required to be released before CERCLA reporting is required.

Superfund Amendments and Reauthorization Act of 1986 (SARA)
SARA 311 Classifications

Chronic (Delayed)

Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>CAS number</u>	<u>Percent by Weight</u>	<u>Reportable quantity</u>
Ethylene glycol	107-21-1	1.0 %	5000 lbs

SARA 313 (TRI Reporting)

<u>Chemical Identity</u>	<u>CAS number</u>	<u>Percent by Weight</u>	<u>Reporting threshold for other uses</u>	<u>Reporting threshold for manufacturing and processing</u>
Ethylene glycol	107-21-1	1.0 %	10000 lbs	25000 lbs

US State Regulations**US. California Proposition 65**

No ingredient regulated by CA Prop 65 present.

Inventory Status**Australia (AICS)**

All components are in compliance with chemical notification requirements in Australia.

Canada (DSL/NDSL)

All components are in compliance with the Canadian Environmental Protection Act and are present on the Domestic Substances List.

China (IECSC)

All components of this product are listed on the Inventory of Existing Chemical Substances in China.

European Union (REACH)

To obtain information on the REACH compliance status of this product, please e-mail REACH@SDSInquiries.com.

Japan (ENCS)

All components are in compliance with the Chemical Substances Control Law of Japan.

Korea (ECL)

All components are in compliance in Korea.

New Zealand (NZIoC)

All components are in compliance with chemical notification requirements in New Zealand.

Philippines (PICCS)

All components are in compliance with the Philippines Toxic Substances and Hazardous and Nuclear Wastes Control Act of 1990 (R.A. 6969).

Switzerland (SWISS)

All components are in compliance with the Environmentally Hazardous Substances Ordinance in Switzerland.

Taiwan (TCSCA)

All components of this product are listed on the Taiwan inventory.

United States (TSCA)

All components of this material are on the US TSCA Inventory.

The information that was used to confirm the compliance status of this product may deviate from the chemical information shown in Section 3.


16. Other information, including date of preparation or last revision

HMIS Hazard ID

Health	<input type="text" value=""/>	<input type="text" value="2"/>
Flammability	<input type="text" value=""/>	<input type="text" value="1"/>
Physical Hazards	<input type="text" value=""/>	<input type="text" value="0"/>

Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe; RNP - Rating not possible; *Chronic health effect

NFPA Hazard ID



Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe; RNP - Rating not possible

- Issue Date:** 03/24/2016
- Version #:** 2.0
- Source of information:** Internal company data and other publically available resources.
- Further Information:** Contact supplier (see Section 1)
- Disclaimer:** As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this product. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with all applicable federal, state, and local regulations remains the responsibility of the user.